

## **Surat Smart City Development Ltd. (SSCDL)**

Bid for
Supply, Installation, Configuration and Integration
Of Networking Equipments
[SSCDL-Network-01-2020]

Last Date of Downloading & Online Submission of Bids Feb 17, 2020

Last Date of Physical Submission of EMD, Bid Fee Feb 25, 2020

Surat Smart City Development Limited
1st Floor, South Zone Office,
Surat Municipal Corporation,
Opp. Satyanagar, Udhna, Surat-394210

## **Notice Inviting Bid**



#### **Surat Smart City Development Limited (SSCDL)**

1st Floor, South Zone Office, Surat Municipal Corporation, Opp. Satyanagar, Udhna, Surat-394210



#### **Notice Inviting**

Bid for Supply, Installation, Configuration and Integration of Networking Equipments
[SSCDL-Network-01-2020]

Bid for Supply, Installation, Configuration and Integration of Networking Equipments is being published by Surat Smart City Development Ltd (SSCDL) online on https://smc.nprocure.com from the bidder meeting the basic eligibility criteria as stated in the bid document.

Bid Fee (Non-refundable)	• Rs. 1,680/- (Rs. 1,500/- + 12% GST) (by DD or Banker's Cheque only)
EMD	<ul> <li>Rs. 30,000/- (by DD or Banker's Cheque only)</li> </ul>
Last date to submit the Online Pre Bid Queries	<ul> <li>Bidders shall have to post queries by email to dmc@suratmunicipal.org on or before 12/02/2020, 16:00 hrs.</li> </ul>
Online Bid End Date (Last Date of Online Submission of Bids with all necessary documents as per tender document requirement in soft copy)	To be submitted online only on <a href="https://smc.nprocure.com">https://smc.nprocure.com</a> on or before 17/02/2020 up to 18:00 hrs.
Submission (in Hard Copy) of Bid Fee, EMD.	<ul> <li>In sealed envelope strictly by RPAD/Postal Speed Post on or before 25/02/2020 up to 18:00 hrs. to the Chief Accounts, Surat Municipal Corporation, Muglisara, Surat – 395003</li> </ul>
Tender Document Availability	<ul><li>https://smc.nprocure.com,</li><li>http://www.suratsmartcity.com/</li></ul>

The right to accept/reject any or all bid(s) received is reserved without assigning any reason thereof.

(Sd/-)

CEO





## INDEX

No	tice Inviting Bid	2
TEC	CHNICAL BID	5
1.	Key Events & Dates	5
2.	Instructions for the Bidder	6
3.	Eligibility Criteria	12
4.	Indicative list of Documents to be submitted	13
5.	General Terms and Conditions	15
6.	Technical (minimum) Specification	21
7.	ANNEXURES TO TECHNICAL BID	32
8	PRICE RID	<b>4</b> 1



## **Surat Smart City Development Ltd. (SSCDL)**

Bid for
Supply, Installation, Configuration and Integration
Of Networking Equipments
[SSCDL-Network-01-2020]

## **Technical Bid**

Last Date of Downloading & Online Submission of Bids Feb 17, 2020

Last Date of Physical Submission of EMD, Bid Fee Feb 25, 2020

Surat Smart City Development Limited
1st Floor, South Zone Office,
Surat Municipal Corporation,
Opp. Satyanagar, Udhna, Surat-394210



**Key Events & Dates** 

Opening of Technical Bids

Opening of Price Bids



## **TECHNICAL BID**

1. Rey Events & Dates	
Event	Target Date
Notice Inviting Tender	SSCDL-Network-01-2020
Bid Fee (Non-refundable)	Rs. 1,680/- (Rs. 1,500 + 12% GST) (by DD or Banker's Cheque only)
EMD	Rs. 30,000/- (by DD or Banker's Cheque only).
Last date to submit the Online Pre Bid Queries	Bidders shall have to post queries by email to dmc@suratmunicipal.org on or before 12/02/2020, 16:00 hrs
Online Bid End Date (Last Date of Online Submission of Bids with all necessary documents as per tender document requirement in soft copy)	To be submitted online only on <a href="https://smc.nprocure.com">https://smc.nprocure.com</a> on or before 17/02/2020 up to 18:00 hrs.
Submission (in Hard Copy) of Bid Fee, EMD.	In sealed envelope strictly by RPAD/Postal Speed Post on or before 25/02/2020 up to 18:00 hrs. to

the Chief Accounts, Surat Municipal Corporation,

To be decided and communicated later
To be decided and communicated later

Muglisara, Surat – 395003



## 2. Instructions for the Bidder

#### 2.1. Availing Bid Documents

Blank bid documents can be downloaded from the web site <a href="https://smc.nprocure.com">https://smc.nprocure.com</a> up to the date and time mentioned in the Online Bid Invitation Notice SSCDL-Network-01-2020.

#### 2.2. Addenda & Corrigenda

If required the Addenda and Corrigenda will be issued and the same will **form the part of the original bid documents** and shall override any contradicting effects in the original bid document.

#### 2.3. Submission of Price Bid and Technical BID

The price bid and the technical bid containing all the relevant supporting documents must be submitted online only on <a href="https://smc.nprocure.com">https://smc.nprocure.com</a> on or before the last date of submission of the bid. No documents except the Bid Fee, EMD to be accepted in hardcopy. It is advised to keep the softcopy of the relevant documents ready and upload the same in advance on <a href="https://smc.nprocure.com">https://smc.nprocure.com</a> with respect to this tender to avoid issues if any.

All the relevant softcopy should invariably follow the (n)Code portal's specific requirements pertaining to file types, file size, file name length, etc.

- o **File Types:** Files with only .pdf, .doc, .txt, .xls, .ppt, .pps, .png, .gif, .jpg, .zip, .rar extension can be uploaded.
- $\circ$  **File name:** It should not be more than 70 characters. Special Characters Like ('% @ < >: \*? | & ~ ^) are not permitted.
- o **File size:** Single file size should not be more than 3 MB.

The bid document (duly signed and stamped) in hard copy shall be submitted by the successful bidder upon intimation from SSCDL/SMC.

#### 2.4. Pre-bid Queries

A prospective Bidder requiring any clarification on the RFP Document may submit his queries, via email, to the following e-mail id on or before **31/05/2018 up to 16:00 hrs.** Email Id for submission of queries: **dmc@suratmunicipal.org** 

The queries must be submitted in the following format:

Bidder's Request for Clarification						
Name and Address of the Organization						
submitting request						
		Tel:				
		Mobile:				
		Fax:				
		Email:				

Sr. No	Bid Reference(s) (Section, Page)	Content of Bid requiring clarification	Points of clarification required

#### 2.5. Bid Fee & Earnest Money Deposit (EMD)

- The bidder should pay non-refundable Bid Fee of Rs. 1,680/- (Rs. 1,500/- + 12% GST) and EMD of Rs. 30,000/- by separate Demand Draft or Banker's Cheque of any scheduled/nationalized bank payable at Surat in favour of Surat Smart City Development Limited.
- Failure to submit Bid Fee, EMD as required shall lead to the bid being rejected summarily.
- **2.6.** The bid should be filled in legibly, clearly indicating the figures and its value in words too.

#### 2.7. Online Submission of the Technical Bid:

The bidder will be required to upload the duly signed, stamped and notarized colour scanned copy of below mentioned documents in the same order of sequence online on smc.nprocure.com during e-tendering process.

- 1. Scan copy of Tender (Bid) Fee
- 2. Scan copy of EMD
- 3. Scan copy of Solvency certificate
- 4. Scan copy of the all supporting documents clarifying compliance to the eligibility criteria as stated in Section-4 Indicative list of Documents to be submitted.
- 5. Scan copy of Bid Format given in Section 7, Annexure to Technical Bid
  - A. Bidder's Details (signed and stamped page no. 32-33)
  - B. Information of Authorized Signatory / Contact Person (signed and stamped page no. 34)
  - C. Authorization Letter from OEM, **Form A** (on OEM's letterhead, Page No. 35).
  - D. Performa of Compliance letter, **Form B** (on Bidder's letterhead, Page No 37).
- 6. Scan copy of duly filled, signed and stamped Technical Specification given in Section – 6 (To be submitted on **OEM's letterhead**)
- 7. Scan copy of duly filled, signed and stamped Technical Specification given in Section - 6 (To be submitted on **Bidder's letterhead**)
- 8. Scan copy of PAN card
- 9. Scan copy of company registration with state government/central government.
- 10. Scan copy of GST Registration Certificate.
- 11. Scan copy of duly signed Tender Document.
- 12. Scan copy of duly signed addendum and Corrigendum, if any.



- 13. Authorization Letter as per Clause-2.26 and as per Format given in Section 7, Annexure to Technical Bid, **E.** Format for Power of Attorney for Signing of the Proposal (mandatory in case tender signatory is other than Owner/Partner/MD/Director/Company Secretary) (Optional)
- 14. Scan copy of any other document not mentioned above but required to be attached as per the tender requirement (Optional).
- 2.8. Demand Draft for E.M.D. & Tender (Bid) fee shall be submitted in electronic format through online mode (by scanning) while uploading the bid. This submission shall mean that E.M.D. & tender fee are received for purpose of opening of the bid. Accordingly offer of those shall be opened whose E.M.D. & tender (bid) fee is received electronically. However, for the purpose of realization of D.D. bidder shall send the D.D. in original through RPAD / Speed post as per Clasue-2.11 below so as to reach to Chief Accountant, SMC within 7 days from the last date of online submission of the bid as per tender notice. Penaltative action for not submitting D.D. in original to shall be initiated and action shall be taken for abeyance of registration and cancellation of E-tendering code for one year. Any documents in supporting of bid shall be in electronic format only through online (by scanning) & hard copy will not be accepted separately.
- 2.9. All documents must be coloured scanned to be seen as original. Scanning in black and white or grey shall not be acceptable.
- 2.10. All documents must be notarized with clearly-displaying stamp, number and name of the notary.
- 2.11. Sealing, marking and submission of the Bid Fee, EMD:

Following documents shall only be submitted in Hard Copy to Surat Smart City Development Limited/SMC by the bidder:

- Earnest Money Deposit (EMD)
- Tender Fee.

The "Bid Fee, EMD" shall be put in an envelope containing Bid Fee, Earnest Money Deposit (EMD) and shall be super scribed as "Bid Fee, EMD"

The envelope must be sealed and super scribed and must be sent as under:

#### Details to be mentioned exactly on sealed envelop **TENDER DETAILS** To, Notice No.: SSCDL-Network-01-2020 The Chief Accountant, Bid for Supply, Installation, **Surat Municipal Corporation**, Configuration and Integration of Mahanagar Seva Sadan, Networking Equipments. Gordhandas Chokhawala Marg, Last date of Online Submission: Muglisara, Surat - 395 003, 17/02/2020 up to 18:00 hrs. Last date of Physical Submission: Gujarat, INDIA. 25/02/2020 up to 18:00 hrs.

The envelope containing EMD, Bid Fee must be sent <u>strictly by Postal Speed Post or</u> <u>Registered Post AD</u> only so as to reach on or before 25/02/2020 up to 18:00 hrs. <u>Bids</u>



received in any other manner or mode (like courier, in person, etc.) will not be considered. SSCDL/SMC won't be responsible for postal delays.

#### **TECHNICAL BID & PRICE BID**

The technical bid & price bid must be submitted online on <a href="https://smc.nprocure.com">https://smc.nprocure.com</a>. It should not to be sent physically, if submitted physically the bid shall be rejected.

- **2.12.** The bidder will be bound by the details furnished to SSCDL/SMC, while submitting the bid or at subsequent stage. In case, any of such documents furnished by the bidder is found to be false at any stage, it would be deemed to be a breach of terms of contract making him/her liable to legal action besides termination of contract.
- **2.13.** Late Bids: Bids not reaching on or before the specified time limit will not be accepted.
- **2.14. Conditional Bids:** All the terms and conditions mentioned herein must be strictly adhered to by all bidders. Conditional tenders shall not be accepted on any ground and shall be subject to rejection without assigning any reason.

#### 2.15. Withdrawal of Bids

Bid once filled in, submitted shall not be allowed to be withdrawn till the validity of the bid remains in force or else the EMD shall be liable for forfeiture.

#### 2.16. Period of Validity

The offer should be valid for acceptance for a minimum period of **120 days** from the date of opening of the Price Bid. If required, SSCDL/SMC may request the bidder to have it extended for a further period.

#### 2.17. Language of Bids

The bids prepared by the bidder shall be in the English language. The supporting documents in language other than English/Hindi/Gujarati must have its English translation (which is to be duly attested by the bidder), for purposes of interpretation of the bid, the English translation shall govern.

#### 2.18. Right To Accept or Reject Any Bid or All Bids

SSCDL/SMC reserves the right to accept or reject any bid and annul the bidding process and reject all bids at any time prior to award of contract, without thereby incurring any liability to the affected bidder or bidders or any obligation to inform the affected bidder or bidders of the ground for SSCDL/SMC's action.

#### 2.19. Firm Prices & Bid Currency

Prices quoted must be firm and final and shall not be subject to any upward modifications, on any account whatsoever. Prices shall be expressed in Indian Rupees (INR) only.

#### 2.20. Costs to be Borne by Bidder

All costs and expenses (whether in terms of time or money) incurred by the bidder in any way associated with the development, preparation and submission of the bid, including but not limited to attendance at meetings, discussions, demonstrations, etc. and providing any additional information required by SSCDL/SMC, will be borne entirely and exclusively by the bidder.

#### 2.21. Acceptance of Terms & Conditions



The bidder will, by taking participation in the bidding process and submitting the bid documents, be deemed to have thoroughly read, studied and understood the bid documents including scope of work, the terms and conditions, instructions, etc. referred there in and the same are acceptable to the bidder.

- **2.22.** All entries in the bid form should be legible and filled clearly. If the space for furnishing information is insufficient, a separate sheet duly signed by the authorized signatory may be attached. However, the interlineations, erasures or overwriting, if any, in the Technical Bid Application must be attested by the person authorized to sign the bids.
- **2.23.** It is to be ensured that the complete information as required by this office may be furnished by the bidders in the prescribed format. Formats submitted with incomplete information and not conforming to the requirements are liable to be rejected.
- **2.24.** The agency will be bound by the details furnished by him/her to SSCDL/SMC, while submitting the bid or at subsequent stage. In case, any of such documents furnished by the agency is found to be false at any stage, it would be deemed to be a breach of terms of contract making him/her liable to legal action besides termination of contract.
- **2.25.** The participation in the online tendering process implies that the bidder have thoroughly read, studied and understood the instructions of the Bid documents, Scope of work, formats as well as the terms and conditions referred there in and the same are acceptable to the bidder.

#### 2.26. Authorized Signatory

For the purpose of submission of the bid, the bidder may be represented by either the Principal Officer (Owner/MD/Director/Company Secretary) or his duly Authorized Representative, in which case he/she shall submit a certificate of authority along with the technical bid. All certificates and documents (including any clarifications sought and any subsequent correspondences) received hereby, shall, as far as possible, be furnished and signed by the authorized representative or the principal officer.

- **2.27. Arithmetical errors will be rectified on the following basis. If there is a discrepancy** between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected. If the supplier does not accept the correction of the errors, its bid will be rejected. If there is a discrepancy between words and figures, the amount in words will prevail.
- 2.28. Disqualifications: A Bidder shall be disqualified and Bids will not be considered if
  - a) Hardcopy envelop does not show on it the reference of bid number and description as denoted and thus gets opened before due date(s) of opening specified in Notice Inviting Bids.
  - b) The Price Bid and Technical Bid is submitted physically which leads to revelation of prices before the due date of opening of the Price Bid.
  - c) The Earnest Money Deposit (EMD) & Bid fee is not deposited in the manner specified above Clause 2.11.
  - d) The Bid documents are not in a language as per Clause 2.17.
  - e) The Bid documents are not signed affixing stamp by the authorized signatory.



- f) The Bid documents submitted are incomplete and/or ambiguous in any respect.
- g) Non-compliance of provisions and requirements of the Bid documents.
- h) Any or all correction(s) or pasted slip(s) is/are not initialled, authenticated by the Bidder.
- i) The Bid documents are not submitted in the manner specified in the bid document.
- j) Eligibility criteria are not met with.
- k) Any form of canvassing/lobbying/influence/query regarding short listing, status, etc. will result in a disqualification.

(Sd/-) CEO Surat Smart City Development Ltd



## 3. Eligibility Criteria

The bidder must possess the requisite experience, strength and capabilities in providing the equipments necessary to meet the broad requirements, as described in the bid document.

The bidder interested in being considered for this bid must meet the following eligibility criteria.

- **3.1.** The bidder should have completed at least 3 years of experience/operation in the field of supply, installation and Commissioning of Network Equipments (like Routers, L3/L2 Managed Switches, Firewall/UTM) from bid start date and should have local office in Surat.
- **3.2.** Bidder should have a minimum average annual turnover not less than Rs. 50 Lacs (Rs. Fifty Lacs) for last three financial years i.e. FY 2018-19, FY 2017-18, FY 2016-17.
- 3.3. The bidder should have completed/ undertaken assignments of Supplying and Implementing Network range of products (Networks Devices like Routers, L3 Switches, Firewall/UTMs, Access Points with Controller, etc.) in last 3 years as on tender publishing date.

Single order worth Rs. 24,00,000 (Twenty-Four lacs)

OR

Two orders worth Rs. 15,00,000 (Fifteen Lacs) each.

OR

Three orders worth Rs. 12,00,000 (Twelve lacs) each.

- **3.4.** The bidder shall be the manufacturer/OEM of the Networking equipments specified. In case the bidder is not manufacturer/OEM, the bidder should be duly authorized by the manufacturer/OEM to supply the goods/equipments by submitting Manufacturer's Authorization in format as per Section 7 Annexure C, Form A.
- 3.5. The bidder should not be black-listed / debarred by any of the Government or Public Sector Units in India as on the date of the submission of the tender.
- 3.6. The bidder should furnish Bid Fee and an Earnest Money Deposit (EMD) as per Clause No. 2.11.
- **3.7.** The bidder should furnish Solvency Certificate amounting 20% of the consideration of the Contract from a scheduled/nationalised bank.

#### Note:

Bidders who wish to participate in this bid will have to register on https://smc.nprocure.com Further bidders who wish to participate in online bids will have to procure Digital Certificate as per Information Technology Act 2000 using which they can sign their electronic bids. Bidders can procure the same from (n) code solutions – a division of GNFC Ltd., or any other agency licensed by Controller of Certifying Authority, Govt. of India. Bidders who already have a valid Digital Certificate need not procure a new Digital Certificate.



## 4. Indicative list of Documents to be submitted

The bidder will be required to upload the duly signed, stamped and notarized colour scanned copy of below mentioned documents online on https://smc.nprocure.com to ascertain the claims made. Following is the indicative list of documents that are to be submitted.

#	Description of Requirement	Proof Required to be Submitted
1.	The bidder should have completed at least 3 years of experience/operation in the field of supply, installation and Commissioning of Network Equipments (like Routers, L3/L2 Managed Switches, Firewall/UTM) from bid start date and should have local office in Surat.	<ol> <li>Copy of work order / Completion certificate/ Contract certificate issued by client clearly specifying Bidders Name, details of Work, Date of issue of respective document.</li> <li>Office Address proof in form of Telephone Bill/Utility Bill/Shops &amp; Establishment Certificate/Property Tax Bill/ or any valid document issued by Government indicating office address</li> </ol>
2.	Bidder should have a minimum average annual turnover not less than Rs. 50 Lacs (Rs. Fifty Lacs) for last three financial years i.e. FY 2018-19, FY 2017-18, FY 2016-17.	Copy of Audited Balance sheet of Last 3 Financial Years/Certificate of Auditor.
3.	The bidder should have completed/ undertaken assignments of Supplying and Implementing Network range of products (Networks Devices like Routers, L3 Switches, Firewall/UTMs, Access Points with Controller, etc.) in last 3 years as on tender publishing date.  Single order worth Rs. 24,00,000 (Twenty- Four lacs)  OR Two orders worth Rs. 15,00,000 (Fifteen Lacs) each.  OR Three orders worth Rs. 12,00,000 (Twelve lacs) each.	Copy of work order / Completion certificate/ Contract / Performance certificate issued by client clearly specifying Bidders Name, details of Work, Date of issue, amount of contract/work order value.
4.	The bidder shall be the manufacturer/OEM of the Networking equipments specified. In the case the bidder is not manufacturer/OEM, the bidder should be duly authorized by the manufacturer/OEM to supply the goods/equipments by submitting Manufacturer's Authorization as per Section 7 Annexure C, Form A.	Submit Authorization letter from OEM as per MAF format at Section – 7, Part – C (Form – A: <b>Authorization Letter from OEM</b> ).

5.	Information of Authorized Signatory /	Self-Declaration in this regard by the			
	Contact Person as per Section–5, Item No 3.	authorized signatory of the bidder.			
6.	The bidder should not be black-listed /	Compliance letter/ Self-declaration /			
	debarred by any of the Government or	Undertaking by bidder as per Section			
	Public Sector Units in India as on the date of	– 7, Form–B.			
	the submission of the tender.				
7.	EMD & Bid Fee.	As per Section 2, Item No 2.11.			
8.	Solvency Certificate amounting 20% of the	Solvency Certificate as per Section –5,			
	consideration of the Contract from a	Item No 5.10.			
	scheduled/nationalised bank.				
9.	Compliance with technical specification as	Duly filled Section – 6 [Technical			
	mentioned in Section – 6	Specification] must be submitted			
		separately on OEM's letter head as			
		well as on Bidder's letter head. The			
		same must be duly signed and			
		stamped by authorized person.			
10.	Product literature	Technical details/brochures /			
		specification sheet of bided products			
11.	Goods & Service Tax Registration Nos.	Copy of the Goods & Service Tax			
	_	(GST) Registration Certificate duly			
		notarized			
* No	* Note: Additional documents other than above if any, required for supporting the claims				

Note: Additional documents other than above if any, required for supporting the claims made by the bidder should be attached.



### 5. General Terms and Conditions

#### 5.1. The prices/charges quoted should also include:

- a. Cost of necessary power cables, signal cables, connectors, controllers and necessary device drivers.
- b. Warranty as specified in Technical Specification section for each item including service and parts/modules. Warranty of particular Item will be start from the date of delivery/supply to SSCDL/SMC.
- c. Delivery & Installation at Various SMC offices located throughout the city or at any other office to be decided by the SSCDL/SMC.
- d. Transit Insurance, Freight and loading, unloading charges up to SMC's site location.
- e. Supplying, Installation, Configuration & Integration with existing LAN & WAN of SMC.
- f. Shifting of Network Equipmets like Network Switches, Network Rack from one location to other location on requirement basis during contract period.

#### 5.2. OEM / Implementation Partner Participation Criteria

- i. The bidder shall be the manufacturer or the authorized service provider or authorized **service partner** of the hardware quoted.
- ii. The bidder will be required to submit a manufacturer's authorization form from all the OEMs stating that the bidder in concern would be bidding for their products/solutions and have to provide "Authorization Letter from OEM" (as per Form 'A') in soft copy online on https://smc.nprocure.com on its letter head duly signed by the authorized signatory.
- iii. Hardware provided must be latest released product from OEM and it must not be under the list end of sale, end of support from OEM till 5 years from date of Delivery/commissioning/activation of services if subscription/support/hardware parts/model is not available/provided from OEM after few years but before the end of contract period than bidder is required to provide equivalent or higher model released by OEM with all features/subscriptions mentioned till the validity of contract period.
- iv. Bidders are required to specify only one specific make and model of each item and provide the details in the Technical bid. Providing more than one option shall not be
- v. As part of Technical Compliance/validation of the features/specifications, if required, SSCDL/SMC may ask bidder for Demonstrations/Proof of concept (PoC) of the product quoted/proposed with full/All features enabled and as per configuration requirement of SSCSL/SMC. In case bidder fails to provide successful Demonstrations/Proof of concept (PoC) of the product as per requirement of SSCDL/SMC, product proposed/quoted will not be considered for further process of tender.





- **5.3.** The bidder has to submit the "**Self-Declaration**" as per the Performa of Compliance Letter (as per **Form 'B'**) in soft copy online on https://smc.nprocure.com on its letter head duly signed by the authorized signatory.
- **5.4.** The offer should be valid for acceptance for a minimum period of **120 days** from the date of opening of the Price Bids. If desired by SSCDL/SMC, it will have to be extended for a further period also.

#### 5.5. Rate Contract:

The above network equipments will be required for connecting various remote offices with SMC HQ. The work for establishing WAN connectivity with these offices has already been awarded. The requirement of these devices will come up as and when the connectivity to these locations is commissioned. Hence, the work order will be issued in staggered manner over a period.

The approved rate of the selected bidder shall be considered as the rates under rate contract and the same will be valid for the period of Two years from date of commissioning/Go-Live of first work order. SMC will use this rate for procurement in desired quantity during the rate validity period i.e. Two years.

- **5.6.** SSCDL/SMC may buy/order full/partial quantity from one/more bidder(s) and may split/ defer/ stagger the order(s)/ deliveries. The quantities shown in the tender are approximate and no claim shall be entertained for variation of quantities being less or more than those mentioned in the bid. The variations in the quantities shall not vitiate the contract. The selected bidder shall be bound to supply additional quantity up to 30% (thirty percent) of tender amount/quantity at the approved rate, in accordance to any instruction, which may be given to him in writing by SSCDL/SMC. The rates quoted by the bidder will be applicable on full / partial /additional quantity also.
- **5.7.** The Bidder may participate in the bid by quoting for one, more or all the items depending on his techno-commercial capability to supply & support that range of products.
- **5.8.** The right to reject accepts any/all Bids(s) without assigning any reason thereof is reserved.
- **5.9.** In case the quoted Item is not available in the market, the bidder will have to supply Higher Version/replacement of that Item in the quoted cost in the same time duration with prior approval of SSCDL/SMC. No "End of Life" product should be quoted to minimize such instances till the bid validity (Make & Model quoted by the bidder should be available till the bid validity, duly supported for spares/OEM support for 5 years).

#### 5.10. Security Deposit:

The successful agency will be required to place Security Deposit @ 5% of the consideration of the Contract by Demand Draft or Banker's Cheque Payable at Surat in favour of Surat Smart City Development Limited of any scheduled/nationalized bank within 10 working days from the date of notice of award of contact, failing which a penalty @ 0.065% of the amount of security deposit will be imposed for delay of each



day. The EMD placed may be considered for conversion towards the security deposit and amount falling short of the required amount shall be payable. No interest shall be paid on Earnest Money Deposit and/ or Security Deposit placed.

#### 5.11. Solvency Certificate

Along with the technical bid documents, the bidder should submit Solvency Certificate amounting 20% of the consideration of the Contract from a scheduled/nationalized bank. The Solvency Certificate should valid and should not be older than one year from the bid start date.

**5.12.** In case, the awardee i.e. the selected agency fails to supply specified quantity and quality of goods in time or the performance of such supply/supplies is/are not found up to the mark or found of an inferior quality vis-à-vis specifications, the security deposit will be forfeited at once.

#### 5.13. Agreement & Undertaking:

The Awardee i.e. the selected agency will have to enter into an Agreement and submit an Undertaking with SSCDL/SMC for supply of goods and its/their installation, Commissioning etc. on a Rs. 300/- stamp paper each of Government of Gujarat at the agency's own cost within 10 (Ten) working days (of SSCDL/SMC) period from the date of Notice of Award. No claims for payments will be entertained without completion of this process.

#### **5.14. TAX LIABILITY**

GST (Goods & Service Tax) has come in existence from 1st July 2017. Contractor / Successful Bidder is bound to pay any amount of GST prescribed by the Govt. of India as per the Terms of Contract agreed upon during the course of execution of this Contract.

During the course of execution of Contract, if there is any change in Rate of GST (Goods & Service Tax) by the Government, the same shall be reimbursed / recovered separately by SSCDL/SMC, subject to the submission of Original Receipt / Proof of the amounts actually remitted by the Successful Tenderer / Contractor to the Competent Authority along with a Certificate from Chartered Accountant of Contractor / Successful Bidder certifying that the amount of GST paid to the Government and the same shall be intimated / submitted / claimed within 30 (Thirty) Days from the date of payment. Remittance of GST within stipulated period shall be the sole responsibility of the Successful Bidder / Contractor, failing which SSCDL/SMC may recover the amount due, from any other payable dues with SSCDL/SMC and decision of Municipal Commissioner shall be final and binding on the Contractor / Successful Bidder in this regard. Further, the non-payment of GST to the Government may lead to the termination of contract and forfeiture of Security Deposit / Performance Guarantee Amount.

If imposition of any other new Taxes/Duties/Levies/Cess or any other incidentals etc. or any increase in the existing Taxes/Duties/Levies/Cess or any other incidentals etc. (excluding GST) are imposed during the course of the contract, the same shall be borne

by the Contractor/Successful Bidder Only, in no case SSCDL/SMC shall be liable for the same.

The contractor will submit the invoice to the SSCDL/SMC having GSTIN of SSCDL/SMC mentioned therein and the taxes shall be shown separately on the face of the invoice so as to claim as ITC by SSCDL/SMC.

#### SURAT SMART CITY DEVELOPMENT LIMITED GST ID 24AAWCS9229G1ZR.

- **5.15.** Technical details/Datasheets of goods to be supplied shall be submitted along with the Bid.
- **5.16.** Manuals relating to Hardware/Peripherals shall be supplied.
- **5.17.** It shall be noted that the lowest rate(s)/price(s) will not be the sole criterion for accepting Bid for any of the goods but emphasis will be given to the quality of the products and even the readiness to offer innovative technology thereof.
- **5.18.** Any offer/Bid not meeting the terms and conditions mentioned hereinabove will be liable for rejection without assigning any reason thereof.

#### 5.19. Delivery schedule:

The successful agency shall deliver, install, configure and integrate the goods as detailed in this Bid within **30 calendar days** from the date of the Work/Purchase order. A penalty of 0.2% of the consideration of contract for a particular item will be charged for delayed supply and installation for delay of each day thereafter.

- **5.20.** The agency shall extend all the benefits to the SSCDL/SMC such as free samples of products, materials, goods, articles including any kind of discount, rebate, commission, incentives normally offered to any other buyer in the form of gift or otherwise as part of the sales promotion scheme(s). If any such sales promotion scheme(s) is /are already launched for the product and is/are in force while the Bid process is on, mention of details of such scheme(s) must be made explicitly in the offer.
- **5.21.** The liability as to any damages and/or loss otherwise to any movable or immovable properties, assets during loading, unloading or otherwise during the period of supply, whether knowingly or unknowingly done or occurred shall be made good forthwith to the SSCDL/SMC by the Awardee agency upon a communication made therefore.
- **5.22.** The contract shall be governed by the Laws in India and shall be subject to the jurisdiction of Surat.
- **5.23.** Bid once filled in, submitted shall not be allowed to be withdrawn till the validity of the bid remains in force or else the EMD shall be liable for forfeiture. The agency is expected to examine the Bid Document carefully. Failure to furnish all information required as per the Bid Document may result in the rejection of the bid.
- **5.24.** The agency will be bound by the details furnished by him/her to SSCDL/SMC, while submitting the bid or at subsequent stage. In case, any of such documents furnished by the agency is found to be false at any stage, it would be deemed to be a breach of terms of contract making him/her liable to legal action besides termination of contract.



**5.25.** On commissioning of the product, the successful agency shall ensure maximum uptime for the product/service during warranty period. The call must be attended within 4 working hours and problem to be resolved within 8 working hours of reporting by either repairing or replacing the Switch/Hardware with same or higher configuration in case of product replacement is required. Failing which a penalty as per below mentioned rate will be deducted from the amount payable and/or security deposit for each day of downtime

Delay >8 Hrs. to 3 working days	Penalty at 0.5% of the product cost per day
Delay beyond 3 working days	Penalty at 1% of the product cost per day

If any component/equipment gives continuous trouble, the bidder shall replace the same with the new compatible component/equipment of the same or higher configuration without any additional cost to the purchaser. Also it is responsibility of bidder coordinate with OEM for logging/Troubleshooting/configuration support/Hardware replacement and any other support required for maximum uptime.

- **5.26.** All goods to be supplied shall be of specified or higher speed/technology/version. The SSCDL/SMC or its representative shall have the right (if it so desires) to test the goods to ascertain their conformity to the specifications. The SSCDL/SMC shall notify to the agency for this purpose & nature.
- **5.27. Terms of Payment:** SSCDL/SMC will not make any advance payment. Payment will be made once the ordered products are delivered and installed. The Security Deposit will be released only after the successful completion of the minimum warranty period of five years.
  - 70% in 15 days of Full Supply.
  - 20% in 15 days of complete installation/configuration/integration/activation or within 30 days of supply/activation in case site condition is not ready due reasons within control of SSCDL/SMC (whichever is earlier)
  - 2.5 % on completion of 1<sup>st</sup> year of warranty.
  - 2.5 % on completion of 2<sup>nd</sup> year of warranty.
  - 2.5 % on completion of 3<sup>nd</sup> year of warranty.
  - 2.5 % on completion of 4<sup>th</sup> year of warranty.
- **5.28.** Chairman, SSCDL/Municipal Commissioner, SMC reserves the right to reject, accept any/all bid(s) without assigning any reason thereof.
- **5.29.** The participation in the online tendering process implies that the bidder have thoroughly read, studied and understood the instructions of the Bid documents, Scope of work, formats as well as the terms and conditions referred there in and the same are acceptable to the bidder.
- **5.30.** The agency will be bound by the details furnished by him/her to SSCDL/SMC, while submitting the tender or at subsequent stage. In case, any of such documents furnished

- by the agency is found to be false at any stage, it would be deemed to be a breach of terms of contract making him/her liable to legal action besides termination of contract.
- **5.31.** The total penalty could be up to 10% of the Consideration of Contract and the decision of the SSCDL/SMC shall be treated as final in such cases.

#### 5.32. Consortium or JV or Sub-contracting

The Bidder is NOT allowed to form Consortium or Joint Venture for any specific service within the scope of the tender. Sub-contracting is also NOT be permitted.

- **5.33.** If it is found that the same firm has submitted multiple bids under different names for the proposed contract, all such tender(s) shall stand rejected and bid deposit of each such firm/establishment shall be forfeited. In addition, such firms/establishments shall be liable, at the discretion of the Chairman, SSCDL/Municipal Commissioner, SMC for further penal action including blacklisting.
- **5.34.** The bidder shall indemnify SSCDL/SMC from and against any costs, loss, damages, expense, claims including those from third parties or liabilities of any kind howsoever suffered, arising or incurred inter alia during and after the Contract period out of:
  - any negligence or wrongful act or omission by the bidder or any third party associated with bidder in connection with or incidental to this Contract; or
  - any breach of terms as stated in the bid document, the bidder's Bid and the Contract with the bidder
  - Any infringement of patent, trademark/copyright or industrial design rights arising from the use of the supplied goods and related services or any part thereof.



## 6. Technical (minimum) Specification

- The Bidder may participate in the bid by quoting for one, more or all the items depending on his techno-commercial capability to supply & support that range of products. Bidders are required to mention Make & Model of the product.
- The bidder can quote only one option (i.e. only one product can be quoted) against each item meeting or exceeding the below mentioned minimum specification.
- The bidder must clearly specify the features of the offered product vis-à-vis specification and deviation if any in the Column-C and Column-D of Table-I respectively.
- The exact make and model of the product offered must be specified in the Table-II provided.
- The technical spec sheet and the product brochure of the product offered should also be submitted along with technical bid.
- In case the space provided is not enough then a separate paper as per the format below can be annexed to the bid. The same must be duly signed and stamped.
- The Technical Specification Sheet must be submitted separately on OEM's letter head as well as on Bidder's letter head (for all items). The same must be duly signed and stamped by authorized person of respective entity.

	Table-I			
Item No.	Description and Minimum Specification	Matched/ [Yes/No]	Deviation from Specification /Remarks if Any	Specify Make and Model
Α	В	С	D	E
1.	48 Port all gigabit L3-Lite/Basic L3 Web Manag	ged Switch [	Cisco or HPE m	ake]
	Ports			
	Minimum 48 x RJ-45 auto-			
	Sensing/negotiating 10/100/1000 ports (IEEE			
	802.3 Type 10BASE-T, IEEE 802.3u Type			
	100BASE-TX, and IEEE 802.3ab Type 1000BASE-T).			
	• Either Minimum 2 x 10G BASE SFP+ ports &			
	Minimum 2 x RJ-45 10G BASE-T ports in			
	combination			
	OR			
	Minimum 4 x 10G BASE SFP+ ports with 2 x			
	10G BASE-T RJ-45 SFP Transceivers Modules			

Supplied with Product from Day one in			
•			
EEE 802.3X flow control.			
ntegrated LEDs for improved visual			
monitoring and analysis.			
ninistrative Switch Management			
Must have IEEE 802.1Q Static & Trunk VLAN			
4090+VLAN IDs) & Port-based VLAN.			
Spanning Tree Protocol (STP) to support			
standard IEEE 802.1D STP, IEEE 802.1w Rapid			
Spanning Tree Protocol (RSTP) for faster			
convergence, and IEEE 802.1s Multiple			
Spanning Tree Protocol (MSTP).			
SNMPv1, v2c, and v3 Configuration and			
management.			
EEE 802.3ad Link Aggregation Control			
Protocol (LACP).			
Pv6 Host, Management, multicast and QoS.			
Built-in switch Web-based GUI configuration			
utility for easy browser-based device			
configuration (HTTP/HTTPS) which Supports			
configuration, system dashboard, system			
maintenance, and monitoring.			
Switch should be able to access via Telnet			
Client or SSH.			
Local password and restricted IP addresses			
or secure access to the switch.			
Switch should have 802.1x authentication			
eature.			
Layer 3 IPv4 and IPv6 static Routing for			
manual routing configuration.			
Provision of Dual flash images to provide			
ndependent primary and secondary			
operating system files for backup while			
upgrading.			
ntuitive web interface to upload/download			
the Switch software/firmware to the switch.			
ntuitive web interface to upload/download			
Configurations to and from the switch.			
	Auto-negotiation for speed, duplex mode and flow control & Manual controls. Auto-MDI/MDIX. EEE 802.3X flow control. Integrated LEDs for improved visual monitoring and analysis. Ininistrative Switch Management Must have IEEE 802.1Q Static & Trunk VLAN 4090+VLAN IDs) & Port-based VLAN. Spanning Tree Protocol (STP) to support standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP). SNMPv1, v2c, and v3 Configuration and management. EEE 802.3ad Link Aggregation Control Protocol (LACP). Pv6 Host, Management, multicast and QoS. Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring. Switch should be able to access via Telnet Client or SSH. Cocal password and restricted IP addresses for secure access to the switch. Switch should have 802.1x authentication eature. Layer 3 IPv4 and IPv6 static Routing for manual routing configuration. Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading. Intuitive web interface to upload/download he Switch software/firmware to the switch. Intuitive web interface to upload/download he Switch software/firmware to the switch. Intuitive web interface to upload/download	Auto-negotiation for speed, duplex mode and flow control & Manual controls. Auto-NDI/MDIX. EEE 802.3X flow control. Integrated LEDs for improved visual monitoring and analysis. Ininistrative Switch Management Must have IEEE 802.1Q Static & Trunk VLAN 4090+VLAN IDs) & Port-based VLAN. Spanning Tree Protocol (STP) to support standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster sonvergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP). SNMPv1, v2c, and v3 Configuration and management. EEE 802.3ad Link Aggregation Control Protocol (LACP). Pv6 Host, Management, multicast and QoS. Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring. Switch should be able to access via Telnet Client or SSH. Local password and restricted IP addresses for secure access to the switch. Switch should have 802.1x authentication eature. Layer 3 IPv4 and IPv6 static Routing for manual routing configuration. Provision of Dual flash images to provide independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while independent primary and secondary operating system files for backup while intuitive web interface to upload/download	Auto-negotiation for speed, duplex mode and flow control & Manual controls. Auto-negotiation for speed, duplex mode and flow control & Manual controls. Auto-MDI/MDIX. EEEE 802.3X flow control. Integrated LEDs for improved visual monitoring and analysis. Ininistrative Switch Management Must have IEEE 802.1Q Static & Trunk VLAN 4090+VLAN IDs) & Port-based VLAN. Spanning Tree Protocol (STP) to support standard IEEE 802.1D STP, IEEE 802.1w Rapid spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple spanning Tree Protocol (MSTP). SIMMPV1, v2c, and v3 Configuration and management. EEE 802.3ad Link Aggregation Control Protocol (LACP). Pv6 Host, Management, multicast and QoS. Built-in switch Web-based GUI configuration utility for easy browser-based device configuration, system dashboard, system maintenance, and monitoring. Bowitch should be able to access via Telnet Client or SSH. Local password and restricted IP addresses or secure access to the switch. Bowitch should have 802.1x authentication eature.  Layer 3 IPv4 and IPv6 static Routing for manual routing configuration. Provision of Dual flash images to provide independent primary and secondary opperating system files for backup while upgrading. Intuitive web interface to upload/download the Switch software/firmware to the switch. Intuitive web interface to upload/download the Switch software/firmware to the switch. Intuitive web interface to upload/download

	<ul> <li>Availability of Port statistics through industry-standard RMON</li> </ul>			
	<ul> <li>Jumbo frame support for packets.</li> </ul>			
	<ul> <li>Broadcast storm control to help eliminate network traffic storms.</li> </ul>			
	<ul> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from particular IP/MAC/Source).</li> <li>Must have Network traffic filtering or network access control using MAC and IP</li> </ul>			
	<ul><li>based ACLs.</li><li>Inbuilt Feature of Dynamic Host</li></ul>			
	Configuration Protocol (DHCP) Sever which simplifies the management of large IP networks and supports client and server system. (Optional).			
	Warranty:			
	Minimum <b>5 Years</b> OEM Direct/Back to back Comprehensive Warranty with parts, modules, software and minimum 1 Year OEM 8x5 technical support.			
	Chassis: 1U, rack-mounting kit included			
	Power: Power supply AC 230 V (50/60 Hz)			
	Proposed Make:			
	Proposed Model/Part Code:			
2.	1G SFP LX Transceiver Module for above 48 Po	ort Gigabit V	Veb Managed S	witches
	Ports	T	<u> </u>	T
	<ul> <li>Single Mode 1G BASE-LX port; Bi-Directional Duplex: full only</li> </ul>			
	Warranty			
	5 Years comprehensive warranty.			
	Proposed Make:			
	Proposed Model/Part Code:			
	Note: Product quoted should be of same make/OEM a Web Managed Switches and must be fully compatible.	•	em No.1: 48 Port C	Gigabit

3.	10G SFP+ LR Transceiver Module for above 48 Port Gigabit Web Managed Switches			
	Ports			
	Single Mode 10G BASE-LR port; Bi-			
	Directional Duplex: full only			
	Warranty			
	5 Years comprehensive warranty.			
	Proposed Make:			
	Proposed Model/Part Code:			
	Note: Product quoted should be of same make/OEM a Web Managed Switches and must be fully compatible.	s proposed Ite	em No.1: 48 Port (	igabit
4.	24 Port L3-Lite/Basic-L3 Web Managed Switch	[Cisco or H	PE make]	
	Ports			
	Minimum 24 x RJ-45 auto-			
	Sensing/negotiating 10/100 ports (IEEE			
	802.3 Type 10BASE-T, IEEE 802.3u Type			
	100BASE-TX).			
	• Either Minimum 2 x 1G BASE SFP ports &			
	Minimum 2 x RJ-45 1G BASE-T ports in			
	combination			
	OR			
	Minimum 4 x 1G BASE SFP ports with 2 x 1G			
	BASE-T RJ-45 SFP Transceivers Modules			
	Supplied with Product from Day one in			
	<ul><li>addition to above fixed 24 ports.</li><li>Auto-negotiation for speed, duplex mode</li></ul>			
	Auto-negotiation for speed, duplex mode     and flow control & Manual for 10M			
	Half/Full/100M Half/Full.			
	Auto-MDI/MDIX.			
	IEEE 802.3X flow control.			
	Integrated LEDs for improved visual			
	monitoring and analysis.			
	Administrative Switch Management			
	Must have IEEE 802.1Q Static & Trunk VLAN			
	(4090+VLAN IDs) & Port-based VLAN.			
	Spanning Tree Protocol (STP) to support			
	standard IEEE 802.1D STP, IEEE 802.1w Rapid			
	Spanning Tree Protocol (RSTP) for faster			
	convergence, and IEEE 802.1s Multiple			
	Spanning Tree Protocol (MSTP).			

management.  IEEE 802.3ad Link Aggregation Control Protocol (LACP).  IPv6 Host, Management, multicast and QoS.  Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP		
IEEE 802.3ad Link Aggregation Control Protocol (LACP).  IPv6 Host, Management, multicast and QoS.  Built-in switch Web-based GUI configuration utility for easy browser-based device configuration, system dashboard, system maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>SNMPv1, v2c, and v3 Configuration and</li> </ul>	
Protocol (LACP).  IPv6 Host, Management, multicast and QoS.  Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry in to the ARP Entry to Static ARP Entry; in to the ARP Entry to Static ARP Entry; in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	management.	
IPv6 Host, Management, multicast and QoS. Built-in switch Web-based GUI configuration utility for easy browser-based device configuration, system dashboard, system maintenance, and monitoring. Switch should be able to access via Telnet Client or SSH. Local password and restricted IP addresses for secure access to the switch. Switch should have 802.1x authentication feature. Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration. Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading. Intuitive web interface to upload/download the Switch software/firmware to the switch. Intuitive web interface to upload/download Configurations to and from the switch. Availability of Port statistics through industry-standard RMON Jumbo frame support for packets. Broadcast storm control to help eliminate network traffic storms. Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source). Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>IEEE 802.3ad Link Aggregation Control</li> </ul>	
Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	Protocol (LACP).	
utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.  • Switch should be able to access via Telnet Client or SSH.  • Local password and restricted IP addresses for secure access to the switch.  • Switch should have 802.1x authentication feature.  • Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  • Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  • Intuitive web interface to upload/download the Switch software/firmware to the switch.  • Intuitive web interface to upload/download Configurations to and from the switch.  • Intuitive web interface to upload/download Configurations to and from the switch.  • Availability of Port statistics through industry-standard RMON  • Jumbo frame support for packets.  • Broadcast storm control to help eliminate network traffic storms.  • Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>IPv6 Host, Management, multicast and QoS.</li> </ul>	
configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.  • Switch should be able to access via Telnet Client or SSH.  • Local password and restricted IP addresses for secure access to the switch.  • Switch should have 802.1x authentication feature.  • Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  • Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  • Intuitive web interface to upload/download the Switch software/firmware to the switch.  • Intuitive web interface to upload/download Configurations to and from the switch.  • Intuitive web interface to upload/download Configurations to and from the switch.  • Availability of Port statistics through industry-standard RMON  • Jumbo frame support for packets.  • Broadcast storm control to help eliminate network traffic storms.  • Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	Built-in switch Web-based GUI configuration	
configuration, system dashboard, system maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	utility for easy browser-based device	
maintenance, and monitoring.  Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entries (Dynamic ARP Entry to Static ARP Entries (Dynamic ARP Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	configuration (HTTP/HTTPS) which Supports	
Switch should be able to access via Telnet Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	configuration, system dashboard, system	
Client or SSH.  Local password and restricted IP addresses for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	maintenance, and monitoring.	
Local password and restricted IP addresses for secure access to the switch.     Switch should have 802.1x authentication feature.     Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.     Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.     Intuitive web interface to upload/download the Switch software/firmware to the switch.     Intuitive web interface to upload/download Configurations to and from the switch.     Availability of Port statistics through industry-standard RMON     Jumbo frame support for packets.     Broadcast storm control to help eliminate network traffic storms.     Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).     Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Switch should be able to access via Telnet</li> </ul>	
for secure access to the switch.  Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	Client or SSH.	
Switch should have 802.1x authentication feature.  Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Local password and restricted IP addresses</li> </ul>	
feature.  • Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  • Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  • Intuitive web interface to upload/download the Switch software/firmware to the switch.  • Intuitive web interface to upload/download Configurations to and from the switch.  • Availability of Port statistics through industry-standard RMON  • Jumbo frame support for packets.  • Broadcast storm control to help eliminate network traffic storms.  • Device must have feature to add/allow Static ARP Entry in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	for secure access to the switch.	
Layer 3 IPv4 and IPv6 Static Routing for manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entry in the ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Switch should have 802.1x authentication</li> </ul>	
manual routing configuration.  Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	feature.	
<ul> <li>Provision of Dual flash images to provide independent primary and secondary operating system files for backup while upgrading.</li> <li>Intuitive web interface to upload/download the Switch software/firmware to the switch.</li> <li>Intuitive web interface to upload/download Configurations to and from the switch.</li> <li>Availability of Port statistics through industry-standard RMON</li> <li>Jumbo frame support for packets.</li> <li>Broadcast storm control to help eliminate network traffic storms.</li> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).</li> <li>Must have Network traffic filtering or network access control using MAC and IP</li> </ul>	Layer 3 IPv4 and IPv6 Static Routing for	
independent primary and secondary operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	manual routing configuration.	
operating system files for backup while upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Provision of Dual flash images to provide</li> </ul>	
upgrading.  Intuitive web interface to upload/download the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	independent primary and secondary	
<ul> <li>Intuitive web interface to upload/download the Switch software/firmware to the switch.</li> <li>Intuitive web interface to upload/download Configurations to and from the switch.</li> <li>Availability of Port statistics through industry-standard RMON</li> <li>Jumbo frame support for packets.</li> <li>Broadcast storm control to help eliminate network traffic storms.</li> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).</li> <li>Must have Network traffic filtering or network access control using MAC and IP</li> </ul>	operating system files for backup while	
the Switch software/firmware to the switch.  Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	upgrading.	
Intuitive web interface to upload/download Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Intuitive web interface to upload/download</li> </ul>	
Configurations to and from the switch.  Availability of Port statistics through industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	the Switch software/firmware to the switch.	
<ul> <li>Availability of Port statistics through industry-standard RMON</li> <li>Jumbo frame support for packets.</li> <li>Broadcast storm control to help eliminate network traffic storms.</li> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).</li> <li>Must have Network traffic filtering or network access control using MAC and IP</li> </ul>	<ul> <li>Intuitive web interface to upload/download</li> </ul>	
industry-standard RMON  Jumbo frame support for packets.  Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	Configurations to and from the switch.	
<ul> <li>Jumbo frame support for packets.</li> <li>Broadcast storm control to help eliminate network traffic storms.</li> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).</li> <li>Must have Network traffic filtering or network access control using MAC and IP</li> </ul>	<ul> <li>Availability of Port statistics through</li> </ul>	
Broadcast storm control to help eliminate network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	industry-standard RMON	
network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Jumbo frame support for packets.</li> </ul>	
network traffic storms.  Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  Must have Network traffic filtering or network access control using MAC and IP	Broadcast storm control to help eliminate	
ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP		
ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	<ul> <li>Device must have feature to add/allow Static</li> </ul>	
by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	ARP Entries (Dynamic ARP Entry to Static	
Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	ARP Entry) in to the ARP Table maintained	
not match switch will not allow traffic flow from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	by Switch which will facilitate IP-MAC	
from that IP/MAC/Source).  • Must have Network traffic filtering or network access control using MAC and IP	Binding base security. (If IP-MAC Entry does	
Must have Network traffic filtering or network access control using MAC and IP	not match switch will not allow traffic flow	
network access control using MAC and IP	from that IP/MAC/Source).	
	<ul> <li>Must have Network traffic filtering or</li> </ul>	
lagged ACI a	network access control using MAC and IP	
based ACLs.	based ACLs.	

	<ul> <li>Inbuilt Feature of Dynamic Host         Configuration Protocol (DHCP) Sever which         simplifies the management of large IP         networks and supports client and server         system. (Optional).</li> <li>Warranty:         Minimum 5 Years OEM Direct/Back to back         Comprehensive Warranty with parts, modules,</li> </ul>			
	software and minimum 1 Year OEM 8x5 technical support.  Chassis: 1U, rack-mounting kit included			
	Power: Power supply AC 230 V (50/60 Hz ) Proposed Make: Proposed Model/Part Code:			
5.	8 Port L3-Lite/Basic L3 Web Managed Switch [	Cisco or HPI	E make]	
	Ports			
	<ul> <li>Minimum 8 x RJ-45 ports with at least 2 x 1G BASE-T Gigabit Ethernet ports and rest 10/100 RJ-45 Fast Ethernet auto-Sensing/negotiating ports</li> <li>Auto-negotiation for speed, duplex mode and flow control &amp; Manual for 10M</li> </ul>			
	Half/Full/100M Half/Full.			
	Auto-MDI/MDIX.  JEEF 993 3V flow product.			
	<ul> <li>IEEE 802.3X flow control.</li> <li>Integrated LEDs for improved visual monitoring and analysis.</li> </ul>			
	Administrative Switch Management			
	<ul> <li>Must have IEEE 802.1Q Static &amp; Trunk VLAN (4090+VLAN IDs) &amp; Port-based VLAN.</li> </ul>			
	<ul> <li>Spanning Tree Protocol (STP) to support standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP).</li> </ul>			
	<ul> <li>SNMPv1, v2c, and v3 Configuration and management.</li> </ul>			
	IEEE 802.3ad Link Aggregation Control Protocol (LACP).			
	IPv6 Host, Management, multicast and QoS.			

	<ul> <li>Built-in switch Web-based GUI configuration utility for easy browser-based device configuration (HTTP/HTTPS) which Supports configuration, system dashboard, system maintenance, and monitoring.</li> <li>Switch should be able to access via Telnet</li> </ul>		
	Client or SSH.		
	<ul> <li>Local password and restricted IP addresses</li> </ul>		
_	for secure access to the switch.		
	<ul> <li>Switch should have 802.1x authentication feature.</li> </ul>		
	Layer 3 IPv4 and IPv6 Static Routing for		
	manual routing configuration.		
	Provision of Dual flash images to provide		
	independent primary and secondary		
	operating system files for backup while		
	upgrading.		
	<ul> <li>Intuitive web interface to upload/download</li> </ul>		
_	the Switch software/firmware to the switch.		
	Intuitive web interface to upload/download		
_	Configurations to and from the switch.		
	<ul> <li>Availability of Port statistics through industry-standard RMON</li> </ul>		
_	Jumbo frame support for packets.		
_	Broadcast storm control to help eliminate		
	network traffic storms.		
	<ul> <li>Device must have feature to add/allow Static ARP Entries (Dynamic ARP Entry to Static ARP Entry) in to the ARP Table maintained by Switch which will facilitate IP-MAC Binding base security. (If IP-MAC Entry does not match switch will not allow traffic flow from that IP/MAC/Source).</li> </ul>		
	<ul> <li>Must have Network traffic filtering or network access control using MAC and IP based ACLs.</li> <li>Inbuilt Feature of Dynamic Host</li> </ul>		
	Configuration Protocol (DHCP) Sever which simplifies the management of large IP networks and supports client and server system. (Optional).		

	Mousents		
	Warranty:		
	Minimum <b>5 Years</b> OEM Direct/Back to back		
	Comprehensive Warranty with parts, modules,		
	software and minimum 1 Year OEM 8x5		
	technical support.		
	Chassis: 1U, rack-mounting kit included		
	<b>Power:</b> Power supply AC 230 V (50/60 Hz )		
	Proposed Make:		
	Proposed Model/Part Code:		
6.	16 Port UnManaged Switch		
	Ports		
	Minimum 16 x RJ-45 auto-		
	Sensing/negotiating 10/100 Fast Ethernet		
	ports		
	Auto-MDI/MDIX.		
	IEEE 802.3X flow control.		
	Integrated LEDs for improved visual		
	monitoring and analysis.		
	Desktop or wall-mounting design.		
	Plug-and-play installation		
	Warranty:		
	Min. 5 Years Comprehensive onsite		
	Replacement warranty with parts & Power		
	Adaptor (If any).		
	Proposed Make:		
	Proposed Model/Part Code:		
7.	8 Port UnManaged Switch		
	Ports		
	Minimum 8 x RJ-45 auto-		
	Sensing/negotiating 10/100 Fast Ethernet		
	ports		
	Auto-MDI/MDIX.		
	IEEE 802.3X flow control.		
	Integrated LEDs for improved visual		
	monitoring and analysis.		
	Desktop or wall-mounting design.		
	Plug-and-play installation		
	Warranty:		



	T			
	Min. <b>5 Years</b> Comprehensive onsite			
	Replacement warranty with parts & Power			
	Adaptor.			
	Proposed Make:			
	Proposed Model/Part Code:			
8.	6U Wall Mount Network Rack (Legrand-Valrac	k ADC- Schi	acidor Pittal N	letrack
0.	APW President make)	k, Ai C- Sciii	ileider, Kittai, iv	etiack,
	Rack Size			l
	6U Wall mount			
	Lock & key with front glass door			
	Powder coated Steel cabinet			
	Accessories to be Supplied with each rack unit			
	Min 1 Cooling Fan			
	Min 1 Cable Manager			
	Min 1 Equipment placement tray			
	Min 5 Socket/Plug Power Strip			
	(With repair/replacement)			
	Rack must be supplied with minimum 1			
	(One) no of standard hardware pack/bag			
	(which includes mounting nut-bolts, cable			
	ties etc.) per each Rack Unit for mounting at			
	least 6 Nos Network/IT equipment.			
	Warranty:			
	Min. 5 Years comprehensive warranty with parts			
	like FAN, Power Strip (repair or replacement)			
	Proposed Make:			
	Proposed Model/Part Code:			
		l .		i e

	Table-II: Summary of Products Proposed				
#	Description	Make, Model, Part Code			
1.	48 Port Gigabit L3-Lite/Basic-L3 Web Managed Switch				
2.	1G SFP LX Transceiver Module for above 48 Port Switch				
3.	10G SFP+ LR Transceiver Module for above 48 Switch				
4.	24 Port L3-Lite/Basic-L3 Web Managed Switch				
5.	8 Port L3-Lite/Basic-L3 Web Managed Switch				
6.	16 Port Unmanaged Switch				
7.	8 Port Unmanaged Switch				
8.	6U Wall Mount Network Rack				



Company stamp:

Place:	Signature of Authorized Person:
Date:	Designation:

Name:



## **Surat Smart City Development Ltd. (SSCDL)**

Bid for
Supply, Installation, Configuration and Integration
Of Networking Equipments
[SSCDL-Network-01-2020]

## **ANNEXURES TO TECHNICAL BID**

Last Date of Downloading & Online Submission of Bids Feb 17, 2020

Last Date of Physical Submission of EMD, Bid Fee Feb 25, 2020

Surat Smart City Development Limited
1st Floor, South Zone Office,
Surat Municipal Corporation,
Opp. Satyanagar, Udhna, Surat-394210.



## 7. ANNEXURES TO TECHNICAL BID

All the documents listed below shall be annexed to the bid in the prescribed formats along with the necessary supporting documents to ascertain the claims made by the bidder.

## Bidder's Details

1	Details of responding firm/c	ompany
a.	Name of the Bidder/Supplier	
b.	Address	
c.	Telephone	Fax:
d.	Website	
e.	Are you a Manufacturer / Authorized dealer / Sub dealer / Any other	
f.	Income Tax Number [PAN]	
g.	Goods & Service Tax (GST) No.	
2	Information about respondi	ng firm / Company
a.	Address of Head Quarter/Head Office	
b.	Address of Registered Office	
C.	Main Office in Gujarat	
d.	Office in Surat	
e.	No. of years of operation in India	
f.	Turnover (figures as per last	Yr1 (2016-17)
	three audited balance sheets	Yr2 (2017-18)
	are to be provided)	Yr3 (2018-19)
3	Details of Contact Person	
a.	Name	
b.	Designation	
C.	Address	
d.	Telephone No.	

e.	Mobile No.			
f.	Fax No.			
g.	E-mail			
4	Details of Authorized Signat	ory		
a.	Name			
b.	Designation			
c.	Address			
d.	Telephone No.			
e.	Mobile No.			
f.	Fax No.			
g.	E-mail			
5	Forum of Business (Select ap		n and provide the Registrati	on Details along
	with attested copies of certif	7		Ţ
#	Forum of Business	Yes/ No	Registration Details (submit attested copies of certificates)	Validity Date
h.	Sole Proprietor? (Registration Number under Shops and Establishment Act.)			
i.	Hindu Undivided Family?			
j.	Partnership Firm?			
k.	Public Limited Company under The Companies Act?			
l.	Private Limited Company under The Companies Act?			
m.	State Govt. owned Undertaking/ Corporation / Enterprise?			
n.	Central Govt. owned Undertaking/ Corporation / Enterprise?			
о.	Co-operative Society?			
	Co-operative society:			

## B. Information of Authorized Signatory / Contact Person

Name	Recent Passport Size
Address	Photograph
Phone No.	
Fax No.	
Mobile No.	Signature
Email	
Web Address	Capacity/Designation
Name	Recent Passport Size
Address	Photograph
Phone No.	
Fax No.	
Mobile No.	Signature
Email	
Web Address	Capacity/Designation





## C. Authorization Letter from OEM

$\Gamma \cap$	6	v	/	$\Lambda$
	R	W		/≙\
				_

#### (To be submitted on OEM's letterhead duly signed by its Authorized signatory)

_		
$\Box$	ato.	•

То The Chief Executive Officer, Surat Smart City Development Ltd. 115, Smart City Cell, Surat Municipal Corporation - Head Quarter, Muglisara, Main Road, Surat - 395003, Gujarat.

Sub: Bid for Supply, Installation, Configuration and Integration of Networking Equipments

[SSCDL-Network-01-2020] - Authorization Letter from OEMs

Ref : Tender No: <No> Dated <DD/MM/YYYY>

Dear Sir/ Madam,

We	_, (name and address of the manufa	acturer) who are established and reputed
manufacturers of	having factories at	(addresses of manufacturing /
development locations) d	lo hereby authorize M/s	(name and address of the bidder)
to bid, negotiate and co	nclude the contract with you agains	t the above mentioned tender for below
mentioned equipment m	anufactured / developed by us.	

#	Product Name	Make & Model
1.	48 Port Gigabit L3-Lite/Basic-L3 Web Managed Switch	
2.	1G SFP LX Transceiver Module for above 48 Port Switch	
3.	10G SFP+ LR Transceiver Module for above 48 Switch	
4.	24 Port L3-Lite/Basic-L3 Web Managed Switch	
5.	8 Port L3-Lite/Basic-L3 Web Managed Switch	
6.	16 Port Unmanaged Switch	
7.	8 Port Unmanaged Switch	
8.	6U Wall Mount Network Rack	

We herewith certify that the above-mentioned equipment / products are neither end of sale nor end of the life nor end of support and we hereby undertake to support these equipments till the successful completion of Warranty/Contract Period for five years from date of delivery/supply/activation.

Yours faithfully,

(Signature of the Authorized Signatory (Signature of the Authorized Signatory

from OEM) from Bidder)

Name Name

Designation Designation

Seal. Seal.
Date: Date: Place: Place:

Business Address: Business Address:

## D. Self-Declaration

## FORM – B

# Performa of Compliance letter (To be submitted on Bidder's letterhead duly signed by Authorized signatory)

То

The Chief Executive Officer,
Surat Smart City Development Ltd.
115, Smart City Cell,
Surat Municipal Corporation - Head Quarter,
Muglisara, Main Road, Surat - 395003, Gujarat.

**Sub**: Compliance with the bid terms and conditions, specifications and Eligibility Criteria **Ref**: Bid for Supply, Installation, Configuration and Integration of Networking Equipments [SSCDL-Network-01-2020]

Dear Sir,

With reference to above referred bid, I, undersigned << Name of Signatory>>, in the capacity of << Designation of Signatory>>, is authorized to give the undertaking on behalf of << Name of the bidder>>.

I/We the undersigned, hereby submit our proposal along with the necessary documents. The information/documents furnished along with the above application are true and authentic to the best of my/our knowledge and belief. I / we, am / are well aware of the fact that furnishing of any false information / fabricated document would lead to rejection of my tender at any stage besides liabilities towards prosecution under appropriate law.

I/We have thoroughly & carefully read, studied and understood the Bid documents and Addenda and Corrigenda (if any) including the technical specification, terms and conditions, instructions, etc. referred there in and the same are acceptable to our company.

We hereby confirm that all our quoted items meet or exceed the requirement and are absolutely compliant with specifications mentioned in the bid document, moreover the items bided are not end of life items.

We hereby confirm that all the components/parts/assembly/software which we shall supply on award of contract shall be original new components /parts/assembly/software from respective OEMs of the products and that no refurbished/duplicate/ second hand components/parts/ assembly / software shall be used.

We also explicitly understand that all quoted items meet technical specification of the bid & that such technical specification overrides the brochures/standard literature if the same contradicts or is absent in brochures.

I/We also state that our company is not black-listed / debarred by any of the Government or Public Sector Units in India as on the date of the submission of the tender

Further, I/we agree to abide by all the terms and conditions as mentioned in the bid document without any condition(s). We have also noted that SSCDL/SMC reserves the right to consider/ reject any or all bids without assigning any reason thereof.

In case of breach of any tender terms and conditions or deviation from bid specification other than already specified as mentioned above, the decision of SSCDL/SMC for disqualification will be accepted by us.



Thanking you,

#### For

- <<Name of the bidder>>
- <<Authorized Signatory>>
- <<Stamp of the bidder>>

# E. Format for Power of Attorney for Signing of the Proposal

(On a Stamp Paper of appropriate value)

(Applicable in case of bid not being signed by the person directly authorized by Board of Firm. In the latter case, please provide a copy of the relevant Board Resolution signed by Company Secretary/ Director authorizing the Signatory.)

		Dated:	
То			
The Chief Executive Officer,			
Surat Smart City Development Ltd.			
115, Smart City Cell,			
Surat Municipal Corporation - Head Quarter,			
Muglisara, Main Road, Surat - 395003, Gujarat			
<b>Ref</b> : Bid for Supply, Installation, Configuration and Integration Network-01-2020]	of Netwo	rking Equipmo	ents [SSCDL-
Dear Sir,			
<bidder's name=""></bidder's>	hereby	authorizes	<designated< td=""></designated<>
•		•	e of <b><bidder's< b=""></bidder's<></b>
name> for the following activity	ties vide it	s Board Resolu	ution/Power of
Attorney attached herewith.			
project including Surat Municipal Corporation and to discuss, no agreement and contract related to Bid for Supply, Installation, Con Equipments [SSCDL-Network-01-2020].	_		• ,
Yours faithfully,			
<signature appropriate="" authority="" bidder="" of="" the=""></signature>			
Name of appropriate authority of the Bidder:			
<signature and="" attorney="" designated="" name="" of="" representative="" the=""></signature>	Bidder fo	or acceptance	of this Power
For			
<name bidder="" of=""> Encl: Board Authorization</name>			
Notarised			



# Surat Smart City Development Ltd. (SSCDL)

# Bid for Supply, Installation, Configuration and Integration Of Networking Equipments [SSCDL-Network-01-2020]

## **Price Bid**

Last Date of Downloading & Online Submission of Bids Feb 17, 2020

Last Date of Physical Submission of EMD, Bid Fee Feb 25, 2020

Surat Smart City Development Limited
1st Floor, South Zone Office,
Surat Municipal Corporation,
Opp. Satyanagar, Udhna, Surat-394210.



## 8. PRICE BID

[Note: Must be submitted online, not to be sent physically]

#	Description	Make, Model	Qty.	Unit Rate exclusive of all taxes	GST (%)	Amount inclusive of all/GST (In words & numbers)
Α	В	С	D	Е	F	G=D*(E + (E*(F/100))
1	48 Port Gigabit L3-Lite/Basic-L3 Web Managed Switch		05			
2	1G SFP LX Transceiver Module for above 48 Port Switch		05			
3	10G SFP+ LR Transceiver Module for above 48 Switch		05			
4	24 Port L3-Lite/Basic-L3 Web Managed Switch		75			
5	8 Port L3-Lite/Basic-L3 Web Managed Switch		75			
6	16 Port Unmanaged Switch		10			
7	8 Port Unmanaged Switch		20			
8	6U Wall Mount Network Rack		150			

Note: Bidders have to fill "0" in "Unit Rate exclusive of all taxes" and "GST" column in case bidders do not want to quote particular item/items.

#### Note:

- 1. The rates (Quoted in Unit Rate Column) should be exclusive of all taxes. The applicable GST should be quoted separately in GST column in Price Bid.
- 2. The taxes at prevailing rate will be considered for payment purpose.